



Release Notes

OpenIG 3.1

Mark Craig

ForgeRock AS
201 Mission St., Suite 2900
San Francisco, CA 94105, USA
+1 415-599-1100 (US)
www.forgerock.com

Copyright © 2012-2017 ForgeRock AS.

Abstract

Notes covering OpenIG prerequisites, fixes, known issues. OpenIG provides a high-performance reverse proxy server with specialized session management and credential replay functionality.



This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivs 3.0 Unported License.

To view a copy of this license, visit <https://creativecommons.org/licenses/by-nc-nd/3.0/> or send a letter to Creative Commons, 444 Castro Street, Suite 900, Mountain View, California, 94041, USA.

ForgeRock® and ForgeRock Identity Platform™ are trademarks of ForgeRock Inc. or its subsidiaries in the U.S. and in other countries. Trademarks are the property of their respective owners.

UNLESS OTHERWISE MUTUALLY AGREED BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.

EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

DejaVu Fonts

Bitstream Vera Fonts Copyright

Copyright (c) 2003 by Bitstream, Inc. All Rights Reserved. Bitstream Vera is a trademark of Bitstream, Inc.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Bitstream" or the word "Vera".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Bitstream Vera" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL BITSTREAM OR THE GNOME FOUNDATION BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the names of Gnome, the Gnome Foundation, and Bitstream Inc., shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from the Gnome Foundation or Bitstream Inc., respectively. For further information, contact: fonts at gnome dot org.

Arev Fonts Copyright

Copyright (c) 2006 by Tavmjong Bah. All Rights Reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of the fonts accompanying this license ("Fonts") and associated documentation files (the "Font Software"), to reproduce and distribute the modifications to the Bitstream Vera Font Software, including without limitation the rights to use, copy, merge, publish, distribute, and/or sell copies of the Font Software, and to permit persons to whom the Font Software is furnished to do so, subject to the following conditions:

The above copyright and trademark notices and this permission notice shall be included in all copies of one or more of the Font Software typefaces.

The Font Software may be modified, altered, or added to, and in particular the designs of glyphs or characters in the Fonts may be modified and additional glyphs or characters may be added to the Fonts, only if the fonts are renamed to names not containing either the words "Tavmjong Bah" or the word "Arev".

This License becomes null and void to the extent applicable to Fonts or Font Software that has been modified and is distributed under the "Tavmjong Bah Arev" names.

The Font Software may be sold as part of a larger software package but no copy of one or more of the Font Software typefaces may be sold by itself.

THE FONT SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF COPYRIGHT, PATENT, TRADEMARK, OR OTHER RIGHT. IN NO EVENT SHALL TAVMJONG BAH BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, INCLUDING ANY GENERAL, SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF THE USE OR INABILITY TO USE THE FONT SOFTWARE OR FROM OTHER DEALINGS IN THE FONT SOFTWARE.

Except as contained in this notice, the name of Tavmjong Bah shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Font Software without prior written authorization from Tavmjong Bah. For further information, contact: tavmjong @ free . fr.

FontAwesome Copyright

Copyright (c) 2017 by Dave Gandy, <http://fontawesome.io>.

This Font Software is licensed under the SIL Open Font License, Version 1.1. This license is available with a FAQ at: <http://scripts.sil.org/OFL>.

Table of Contents

1. What's New in OpenIG	1
1.1. What's New in OpenIG 3.1.1	1
1.2. What's New in OpenIG 3.1.0	1
2. Before You Install	5
2.1. JDK Version	5
2.2. Web Application Containers	5
3. Changes and Deprecated Functionality	6
3.1. Important Changes to Existing Functionality	6
3.2. Deprecated Functionality	6
3.3. Removed Functionality	7
4. Fixes, Limitations, and Known Issues	8
4.1. Fixes	8
4.2. Limitations	9
4.3. Known Issues	9
5. Documentation Updates	11
6. How to Report Problems and Provide Feedback	12
7. Support	13

Chapter 1

What's New in OpenIG

Before you install OpenIG or update your existing OpenIG installation, read these release notes.

1.1. What's New in OpenIG 3.1.1

Important

OpenIG 3.1.1 is a maintenance release that resolves a number of issues. It is recommended that you update to this release to take advantage of important functional fixes. ForgeRock customers can contact support for help and further information.

This maintenance release introduces the following improvement:

OpenIG now provides an `array(strings...)` function (OPENIG-474).

The `array()` function returns an array given a series of strings. This function is useful when constructing a string array argument to pass to the `join()` function as in the following example expression that joins the first values of two request headers with a space:

```
${join(array(exchange.request.headers['part_1'][0],  
             exchange.request.headers['part_2'][0], ' '))}
```

1.2. What's New in OpenIG 3.1.0

OpenIG 3.1.0 fixes a number of issues, and provides the following additional features.

- OpenIG can now store session information in encrypted JSON Web Token (JWT) cookies on the user-agent (OPENIG-224, OPENIG-278). By default, OpenIG continues to back session information with HttpSession from the container where OpenIG runs.

With this change, you can specify the session storage at the global level, or in a particular route configuration. For details, see `JwtSession` in the *Reference* and *Setting Up Keys For JWT Encryption* in the *Gateway Guide*.

- OpenIG now allows you to inline configuration objects (OPENIG-311), to omit "config" fields when all values are optional (OPENIG-300), to omit the "objects" field from the "heap" (OPENIG-380), and even to omit the "heap" when it is empty or would only contain a single handler (OPENIG-329).

When you bring an object inline, you no longer need to specify the "name".

For example, suppose your former `config.json` file looks like this:

```
{
  "heap": {
    "objects": [
      {
        "name": "Chain",
        "type": "Chain",
        "config": {
          "filters": [
            "ReplaceHostFilter"
          ],
          "handler": "Router"
        }
      },
      {
        "name": "ReplaceHostFilter",
        "type": "HeaderFilter",
        "config": {
          "messageType": "REQUEST",
          "remove": [
            "host"
          ],
          "add": {
            "host": [
              "example.com"
            ]
          }
        }
      }
    ],
    {
      "name": "Router",
      "type": "Router",
      "config": {}
    }
  ],
  "handler": "Chain"
}
```

OpenIG now lets you rewrite the `config.json` file like this:

```
{
  "handler": {
    "type": "Chain",
    "config": {
      "filters": [
        {
          "type": "HeaderFilter",
          "config": {
            "messageType": "REQUEST",
            "remove": [
              "host"
            ],
            "add": {
              "host": [
                "example.com"
              ]
            }
          }
        }
      ],
      "handler": {
        "type": "Router"
      }
    }
  }
}
```

Examples in the documentation now use streamlined configurations where it makes sense.

- OpenIG now supports object decorators (OPENIG-340). Decorators allow you to define heap objects that decorate other objects, adding the new behavior that the decorator provides.

OpenIG provides the following decorators out of the box.

- A CaptureDecorator that extends what the CaptureFilter could do to capture requests, responses, and exchange data on any decorated object (OPENIG-299, OPENIG-301)
- A TimerDecorator that records times to process the exchange through any decorated object (OPENIG-352, OPENIG-353)
- An AuditDecorator that allows you to audit operation for any decorated object.

For detailed information about decorators, see the *Reference on Decorators* in the *Reference*.

- OpenIG now provides a publish-and-subscribe audit framework and a sample monitoring handler that returns basic statistics (OPENIG-359, OPENIG-386). To learn more, start by reading the chapter about the *OpenIG Audit Framework* in the *Gateway Guide*.
- OpenIG script configurations can now include arguments (OPENIG-240).
- The OAuth2ClientFilter and OAuth2ResourceServerFilter now cache data to avoid unnecessarily calls to the provider (OPENIG-350).

- OpenIG uses improved object names in log messages that make it easier to identify the source of the message (OPENIG-358, OPENIG-371).
- The OpenIG Exchange now provides information about the client (OPENIG-333).

For details see the *Reference* on *ClientInfo* in the *Reference*.

Chapter 2

Before You Install

This chapter covers requirements for running OpenIG software.

Tip

If you have a special request to support a component or combination not listed here, contact ForgeRock at info@forgerock.com.

2.1. JDK Version

This release of OpenIG requires Java Development Kit 6, 7, or 8. ForgeRock recommends the most recent update to ensure you have the latest security fixes.

If you install an OpenAM policy agent in the same container as OpenIG, then you must use a Java release that is supported with the policy agent as well.

2.2. Web Application Containers

OpenIG runs in the following web application containers.

- Apache Tomcat 7
- Jetty 8 (8.1.13 or later)

You must deploy OpenIG to the root context of the container. Deployment in other context causes unexpected results, and cannot be supported.

OpenIG expressions depend on Unified Expression Language 2.2, which is available in containers that support Servlet 3.0 or later. Some expressions can lead to a `java.lang.NoSuchMethodError` in containers that support only Servlet 2.5 (and EL 2.1).

See the *Guide to OpenIG* section, *Configuring Deployment Containers* in the *Gateway Guide*, for details on setting up your web application container.

Chapter 3

Changes and Deprecated Functionality

This chapter covers both major changes to existing functionality, and also deprecated and removed functionality.

3.1. Important Changes to Existing Functionality

OpenIG 3.1 includes configuration changes compared to OpenIG 3.0.0. See Section 3.2, "Deprecated Functionality" for a list of configuration changes resulting in deprecation of earlier features.

3.2. Deprecated Functionality

This release deprecates the following configuration settings. Deprecation is defined in the *Reference* appendix on *ForgeRock Product Interface Stability* in the *Reference*.

Table 3.1. Configuration settings

Configuration Object	Deprecated in the <i>Reference</i> Settings	Newer Evolving in the <i>Reference</i> Settings
CaptureFilter in the <i>Reference</i>	Entire object	Use a CaptureDecorator in the <i>Reference</i> instead
gateway servlet in the <i>Reference</i>	"handlerObject"	New name: "handler"
	Deprecated format: "heap": { "objects": [configuration object, ...] }	New format: "heap": [configuration object, ...]
HttpClient in the <i>Reference</i>	"keystore"	Replaced by "keyManager", which takes one or more KeyManager in the <i>Reference</i> references
	"truststore"	Replaced by "trustManager", which takes one or more TrustManager in the <i>Reference</i> references
OAuth2ResourceServerFilter in the <i>Reference</i>	"enforceHttps"	New name: "requireHttps"
	"httpHandler"	New name: "providerHandler"
	"requiredScopes"	New name: "scopes"

Configuration Object	Deprecated in the <i>Reference</i> Settings	Newer Evolving in the <i>Reference</i> Settings
RedirectFilter	Entire object	Use LocationHeaderFilter in the <i>Reference</i> instead
Route in the <i>Reference</i>	Deprecated format: "heap": { "objects": [configuration object, ...] }	New format: "heap": [configuration object, ...]

This release deprecates the following API classes, which are likely to be removed in a future release.

- org.forgerock.openig.filter.CaptureFilter
- org.forgerock.openig.heap.NestedHeaplet

3.3. Removed Functionality

No functionality has been removed in this release.

Chapter 4

Fixes, Limitations, and Known Issues

OpenIG issues are tracked at <https://bugster.forgerock.org/jira/browse/OPENIG>. This chapter covers the status of key issues and limitations at the time of release.

4.1. Fixes

This section lists important fixes.

4.1.1. Key Fixes in OpenIG 3.1.1

The following issues were fixed in this release:

- OPENIG-589: Backport CHF-52 - MutableUri doesn't preserve encoded values when updating a field value
- OPENIG-587: OpenIG can not connect to TLSv1.2 (TLSv1.1) secured resources
- OPENIG-503: Fix resource leak on route loading
- OPENIG-491: Using groovy script embedded in json route doesn't work on windows
- OPENIG-470: Connections are not released after modifying HttpClient connections pool size
- OPENIG-454: Capture decorator impacts the entity returned in GET
- OPENIG-426: Multiple Host header
- OPENIG-315: POST JSON payload not delivered unless CaptureFilter used

4.1.2. Key Fixes in OpenIG 3.1.0

The following issues were fixed in this release:

- OPENIG-370: Log output often includes irrelevant or duplicated information
- OPENIG-368: OAuth2ClientFilter rebases client endpoint against possibly rebased request.uri
- OPENIG-331: Moving a file in Routes may result in no route configured

- OPENIG-325: Allow scripts and AssignmentFilters to update exchange.request.uri
- OPENIG-312: Use Jackson for better messages about configuration errors in JSON
- OPENIG-119: RedirectFilter should handle HTTP 301
- OPENIG-85: SqlAttributesFilter throws SQLException: Invalid operation for forward only resultset
- OPENIG-78: SqlAttributesFilter throws SQLException: Invalid column index
- OPENIG-56: Temporary files leak
- OPENIG-30: OpenIG to protect multiple apps at one location

4.2. Limitations

For HTTPS, OpenIG can check server certificates. However mutual authentication, where OpenIG presents its client certificate, is not supported if the client certificate is not the first certificate in the HttpClient key store.

OpenIG scripts are not sandboxed, but instead have access to anything in their environment. You must make sure that the scripts that OpenIG loads are safe.

When acting as an OpenID Connect 1.0 relying party, OpenIG does not support dynamic registration.

4.3. Known Issues

This section lists important issues that were not resolved at the time of release.

4.3.1. Known Issues in OpenIG 3.1.1

The following known issues remained open at the time this release became available:

- OPENIG-647: SSL and JDK1.6 - handshake failures
- OPENIG-322: Cannot access both an OpenAM (self-signed) and a Google HTTPS endpoint
- OPENIG-290: Null pointer exception when capturing SAML federation response
- OPENIG-234: Federation doesn't work if we used incomplete user in IDP

4.3.2. Known Issues in OpenIG 3.1.0

The following known issues remained open at the time this release became available:

- OPENIG-322: Cannot access both an OpenAM (self-signed) and a Google HTTPS endpoint
- OPENIG-290: Null pointer exception when capturing SAML federation response
- OPENIG-258: OpenIG doesn't shutdown properly when protected by a Tomcat J2EE agent
- OPENIG-234: Federation doesn't work if we used incomplete user in IDP

Chapter 5

Documentation Updates

The following table tracks changes to the documentation from the release of OpenIG 3.1.0:

Table 5.1. Documentation Change Log

Date	Description
2018-01-25	Refreshed formatting.
2015-09-18	Release of OpenIG 3.1.1. Updates to release notes.
2014-12-12	Initial release of OpenIG 3.1.0.

Chapter 6

How to Report Problems and Provide Feedback

If you have questions regarding OpenIG that are not answered by the documentation, there is a mailing list which can be found at <https://lists.forgerock.org/mailman/listinfo/openig> where you are likely to find an answer.

If you have found issues or reproducible bugs within OpenIG, report them in <https://bugster.forgerock.org>.

When requesting help with a problem, include the following information:

- Description of the problem, including when the problem occurs and its impact on your operation
- Machine type, operating system version, web container and version, Java version, and OpenIG release version, including any patches or other software that might be affecting the problem
- Steps to reproduce the problem
- Any relevant logs or stack traces

Chapter 7

Support

You can purchase OpenIG support, subscriptions and training courses from ForgeRock and from consulting partners around the world and in your area. To contact ForgeRock, send mail to info@forgerock.com. To find a partner in your area, see <https://forgerock.com/>.